



**TECHNICAL DESCRIPTION** S800-Vor6\_TB\_US - 13.10.2017 - [www.vsamerica.com](http://www.vsamerica.com)

## Series 800

### Preliminary remark - wardrobe.

Series 800 element cabinets with swing doors can be equipped from 4FH as wardrobe cabinets. 3 different wardrobe systems are used, depending on the width and depth dimensions.

[1] Width less than  $19\frac{3}{4}$ " , depth =  $16\frac{3}{4}$ " : Centrally positioned 3-point hook under the hat shelf (max. load 35 kg).

[2] Width from  $19\frac{3}{4}$ " , depth =  $16\frac{3}{4}$ " : Pull-out wardrobe rod under the hat shelf (max. load 6 kg).

[3] Width from  $15\frac{3}{4}$ " , depth =  $22\frac{7}{8}$ " : Laterally positioned wardrobe bar under the hat shelf (max. load 50 kg).

Wardrobe cabinets are equipped with plastic ventilation outlets [4] on the top and bottom edges of the door. Hat shelves [5] are located in 4FH-high cabinets at position 3FH and in 5FH- and 6FH-high cabinets at position 4FH. 6FH cabinets also have an additional adjustable shelf insert.

**Construction:** Models from a height of  $77\frac{5}{8}$ " or models with drawers and/or pullouts (DGUV Regel 108-007) must be secured to the wall or floor.